



HS/400LK

**Rivestimento in legno  
tinta noce**

**Covering in solid wood  
ancient-looking walnut**

 **Chiave a Doppia Mappa**

- Struttura monoblocco in lamiera d'acciaio dello spessore di 2 mm.
- Spessore totale del battente 50 mm.
- Serratura di sicurezza a 6 leve con chiave a doppia mappa (2 chiavi in dotazione).
- Estrazione della chiave impossibile a catenacci rientrati.
- 5 catenacci in acciaio nichelato Ø 22 mm.
- Rastrelliera e base in legno massello verniciato.
- Tesoretto interno portamunizioni con serratura a cilindro.
- Fori di ancoraggio sulla base e sullo schienale (4+4).

**HS/400LK:** • con tesoretto - 7 fucili

**HS/600LK:** • con tesoretto - 11 fucili

 **Double-Bitted Key**

- One-piece steel construction of 2 mm thickness.
- Total thickness (with lock panel): 50 mm.
- Security lock with 6 levers and double-bitted key (2 keys supplied).
- Key-retaining lock in open position.
- 5 nickel-plated steel bolts Ø 22 mm.
- Painted solid wood supports and base for rifles.
- Internal security box with cylinder lock.
- Pre-drilled anchor holes on floor and wall mounting (4+4).

**HS/400LK** • with sec. box - 7 rifles

**HS/600LK:** • with sec. box - 11 rifles



Art Code	Misure esterne mm. External dim. mm.			Misure interne mm. Internal dim. mm.			Dim. porta mm. Door dim. mm.		Numero catenacci Number of bolts		Peso Weight	Litri Volume
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Oriz/Horiz	Vert	Kg	Lt
<b>HS/400LK</b>	1605	450	370	1300*	360	265	1410	280	3	1+1	70	134
<b>HS/600LK</b>	1605	625	370	1300*	530	265	1410	430	3	1+1	89	197

\* Esclusa l'altezza della cassetta interna

\* Excluding the high of security box